



MENDE | thin particleboard



THE THIN PANEL THAT DELIVERS QUALITY AND SAVINGS

Mende is a versatile, cost-effective thin particleboard from Flakeboard that can easily be customized to meet a broad range of applications.

Its high quality thin panel construction is ideal for a variety of applications. Produced in 4' wide sheets in a variety of lengths and thicknesses, these panels are popular unfinished or as an excellent substrate for wood veneers.

Mende can also be upgraded with a wide array of decorative finishes, including TFM (melamine), paper overlay, paint and direct print finishes. For no added urea-formaldehyde projects, request Mende VESTA.

General Information	Mende
Thickness (mm)	3.2 to 8.0
Sanding (mm)	Minimum 2.8 to +/- 0.1 tolerance
Density (pcf)	45
Average MOR (psi)	2100
Average MOE (psi)	300,000
Average Internal Bond (psi)	80

The above physical properties are based on averages of normal production.



Le symbole d'un développement forestier responsable
SW-COC-000444
© 1996 FSC

- Product suitability for a particular application is the responsibility of the fabricator or end user
- Complies with CPA EPPS 3-08 and CCR 93120.2(a) (CARB Composite Wood ATCM Phase 1 Formaldehyde Emission Limits)
- Material Safety Data Sheets are available upon request
- All panels are approved for use in interior, non-structural applications
- Contains 100% Recycled/Recovered Wood Content
- Conforms to formaldehyde emission requirements for particleboard in ANSI A208.1-2009 Table B and HUD 24 CFR Part 3280



CPA-3-08 Specification
California ARB Approved
Third Party Certifier TPC-1

