



# MENDE | thin particleboard



## THE THIN PANEL THAT DELIVERS QUALITY AND SAVINGS

Mende is a versatile, cost-effective thin particleboard from Flakeboard that can easily be customized to meet a broad range of applications.

Its high quality thin panel construction is ideal for a variety of applications. Produced in 4' wide sheets in a variety of lengths and thicknesses, these panels are popular unfinished or as an excellent substrate for wood veneers.

Mende can also be upgraded with a wide array of decorative finishes, including TFM (melamine), paper overlay, paint and direct print finishes. For no added urea-formaldehyde projects, request Mende VESTA.

General Information	Mende
Thickness (mm)	3.2 to 8.0
Sanding (mm)	Minimum 2.8 to +/- 0.1 tolerance
Density (pcf)	45
Average MOR (psi)	2100
Average MOE (psi)	300,000
Average Internal Bond (psi)	80

The above physical properties are based on averages of normal production.

- Product suitability for a particular application is the responsibility of the fabricator or end user
- Complies with CPA EPPS 3-08 and CCR 93120.2 (California ARB Composite Wood ATCM Phase 1 Formaldehyde Emission Limits)
- Material Safety Data Sheets are available upon request
- All panels are approved for use in interior, non-structural applications
- Contains 100% Recycled/Recovered Wood Content
- Conforms to formaldehyde emission requirements for particleboard in ANSI A208.1-2009 Table B and HUD 24 CFR Part 3280

### CALIFORNIA PROPOSITION 65 REQUIREMENT

Warning: Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection.



R20110301